

## H3C

### PC-Local

---

```
interface GigabitEthernet1/0/23
```

```
description #
```

```
port access vlan 44
```

---

### UP-Link

```
interface GigabitEthernet1/0/24
```

```
port link-type trunk
```

```
port trunk permit vlan 1 3 10 to 12 15 44 96 98 149
```

```
description #C2960G-OCS-FLR2-R202-10.0.0.57/Gi0/1)#
```

---

### Access Pointe

```
interface Ethernet1/0/1
```

```
poe enable
```

```
port link-type trunk
```

```
port trunk permit vlan 1 3 10 96 98
```

```
port trunk pvid vlan 96
```

```
description APG-DORMG-CHONG-R106-172.16.82.161
```

---

## CISCO

## PC-Local

```
interface FastEthernet0/22  
  
switchport access vlan 21  
  
switchport mode access  
  
spanning-tree portfast
```

---

## UP-Link

```
interface GigabitEthernet0/2  
  
description #Link C6500-VSS_Backbone-158.108.252.2/Gi2/4/25#  
  
switchport trunk allowed vlan 1,3,10,21,96,98  
  
switchport mode trunk
```

---

## Access Pointe

```
interface FastEthernet0/1  
  
description AP1231G-COOP-KU_HOME-SAVING_COOPERATIVE_1-172.16.23.1  
  
switchport trunk native vlan 96  
  
switchport trunk allowed vlan 1,3,10,96,98  
  
switchport mode trunk  
  
spanning-tree portfast
```